



CUSHMAN®

SHUTTLE™ 8



EFFICIENT AND PRODUCTIVE HIGH VOLUME TRANSPORTATION.

The Cushman® Shuttle™ 8 is perfect for transporting large groups of people throughout any facility. With six forward-facing seats and two rear-facing seats, the Shuttle 8 can move up to eight people with ease. Choose between an energy-efficient 72V AC electric drivetrain or powerful 13.5 hp EFI gas engine. Features like a large canopy, ergonomically-designed seating, and dependable performance keep guests and workers happy.

LET'S WORK.®

MARSCARS LLC

**13.5HP
EFI GAS**

**72V
AC ELECTRIC
DRIVETRAIN**

**8
PERSON
SEATING
CAPACITY**

www.CushmanCalifornia.com



CUSHMAN[®] SHUTTLE™ 8



HEADLIGHTS



BENCH SEATING

RACK-AND-PINION
STEERING

OPTIONS & ACCESSORIES

- Rearview Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Pinstripes
- On Board Charger
- Body Color (Forest Green, White, Ivory, Black or Custom Options)
- Turn Signal with Four-Way Flashers
- Brakelights
- LED Headlights
- CE Kit (gas only)



COVERED WITH THE 2-YEAR CUSHMAN
CARE TOTAL PROTECTION WARRANTY

	ELECTRIC MODEL	EFI GAS MODEL
BODY & CHASSIS		
FRAME	Welded Steel w/ DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOR	Patriot Blue	
DIMENSIONS		
OVERALL LENGTH	167.5 in (425 cm)	
OVERALL WIDTH	49.5 in (126 cm)	
OVERALL HEIGHT	45.5 in (116 cm) (w/o Roof) / 76.0 in (193 cm) (w/ Struts & Roof)	
WHEEL BASE	123.4 in (313 cm)	
WHEEL TRACK	36.0 in (91 cm) Front / 38.0 in (97 cm) Rear	
GROUND CLEARANCE	3.0 in (8 cm)	
CARGO DECK CAPACITY	400 lb (181 kg)	
POWER		
POWER SOURCE	72V DC	4-Cycle, 24.5 ci (401cc)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	22.4 hp (16.7 kW) Intermittent	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	72V	N/A
BATTERY (QTY/TYPER)	Six, 12 Volt Deep Cycle	Starter/Generator. Solid State Reg.
BATTERY CHARGER	1000 Watt, 72V, 120/230V VAC UL Listed	One, 12V Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replacable Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	6 Gallon (22 L) Tank
SPEED CONTROLLER	350 Amp AC	N/A
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse	Forward - Reverse
REAR AXLE RATIO	17:1	11.47:1 (Forward) 14.35:1 (Reverse)
PERFORMANCE		
SEATING CAPACITY	8-Person	
WEIGHT W/O BATTERIES	1203 lb (546 kg)	N/A
CURB WEIGHT	1695 lb (769 kg)	1265 lb (574 kg)
VEHICLE LOAD CAPACITY	1600 lb (726 kg)	
BED LOAD CAPACITY	400 lb (181 kg)	
OUTSIDE CLEARANCE CIRCLE	33 ft (10 m)	33 ft (10 m)
SPEED	16.5 mph ± 0.5 mph (26.4 kph ± 0.8 kph) (High Speed)	16 mph ± 0.5 mph (26 kph ± 0.8 kph)
	12 mph ± 0.5 mph (19.3 kph ± 0.8 kph) (Low Speed)	
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	4-Wheel Hydraulic Brakes Front Disk, Rear Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TIRES (FRONT & REAR)	215/60-8	215/60-8

Mars Cars LLC
Call us! (714) 847-7673
www.CushmanCalifornia.com

www.cushman.com

©2019 Textron Specialized Vehicles Inc.
Features and specifications of the vehicles are subject to change without notice.
Vehicle as photographed may include options not included on base model.

82305-G5 (Rev. 12/2018)