

HAULER® 4X4

EXCEED YOUR WORK LIMITS

Built with plenty of muscle, the Cushman® Hauler® 4x4 is equipped to attack your toughest jobs. An impressive 2,000-lb towing capacity, 1,500-lb vehicle payload, four-wheel independent suspension and a top speed of 25 mph, make the Hauler 4x4 ideal for transporting crew and cargo around your facility. Stacked full of standard features including seatbelts, ROPS and doors, your crew will arrive safely, ready to work. With power and performance like that, the Hauler 4x4 makes everything within reach.

LET'S WORK.®

50HP GAS
OR
25HP DIESEL

1500LB LOAD CAPACITY

2000LB TOWING CAPACITY 14.68 CU. FT. BED CAPACITY



www.CushmanCalifornia.com






CUSHMAN HAULER 4X4











STANDARD FEATURES:

- ROPS
- Headrest
- Seatbelts Half Doors
- Glove Box
- Multi-Function Display
- 12-Volt Outlet
- All Terrain Tires
- Side Fill Gas Tank
- Headlights
- Taillights
- Brakelights
- Locking Rear Differential
- Horn
- Lower Brushguard

OPTIONS & ACCESSORIES:

- Power Steering
- Full Windshield with Air Vents
- Glass Windshield
- Canopy
- Center Seat Console
- Underseat Storage Rear View Mirror
- Sun Visor
- Grille Guard
- Headlight Guard · Rear Bumper Kit
- · Back Up Alarm
- 4500 lb WARN Winch

	GAS	DIESEL
BODY & CHASSIS		
FRAME	Welded Steel with E-Shield™ ecoat plus DuraShield™ Powder Coat	Welded Steel with E-Shield™ ecoat plus DuraShield™ Powder Coat
BODY & FINISH	TPO Molded in Color	TPO Molded in Color
STANDARD COLOR	Dynamic Charcoal	Dynamic Charcoal
DIMENSIONS		
OVERALL LENGTH	126 in (320 cm)	126 in (320 cm)
OVERALL WIDTH	63 in (160 cm)	63 in (160 cm)
OVERALL HEIGHT (WITH CANOPY)	74 in (188 cm)	74 in (188 cm)
WHEEL BASE	85 in (216 cm)	85 in (216 cm)
FRONT WHEEL TRACK	51 in (129.5cm)	51 in (129.5 cm)
REAR WHEEL TRACK	51 in (129.5 cm)	51 in (129.5 cm)
GROUND CLEARANCE	10.75 in (27.4 cm)	10.75 in (27.4 cm)
CARGO BOX CAPACITY	14.68 cu ft (0.42 cu. m)	14.68 cu ft (0.42 cu. m)
POWER		
POWERTRAIN	Whisper Quiet 50 HP, 812 cc, 4 Stroke Gas Engine	25 HP (18.6 kW), 1.03L Liquid Cooled, 3 Cylinder Diesel Engine
VALVE TRAIN	3 Cylinder DOHC	3 Cylinder
HORSEPOWER (KW)	50 HP, (37.3 kW)	25 HP, 1028 cc
ELECTRICAL SYSTEM	12V, Alternator	12V, Alternator
BATTERY (QTY/TYPE)	One 12-Volt Maintenance Free	One 12-Volt Maintenance Free
KEY OR PEDAL START	Key	Key
OIL FILTER	Automotive, Screw On	Automotive, Screw On
COOLING SYSTEM	Liquid with Fan	Liquid with Fan
FUEL CAPACITY	10 gal (37.9 L)	10 gal (37.9 L)
DRIVETRAIN	Continuously Variable Transmission (CVT)	Continuously Variable Transmission (CVT
TRANSAXLE	2/4WD Front, Selectable Locking Rear	2/4WD Front, Selectable Locking Rear
GEAR SELECTION	Mechanical, Steering Column Mounted	Mechanical, Steering Column Mounted
FRONT/REAR AXLE RATIO	3.1:1	3.1:1
PERFORMANCE		
SEATING CAPACITY	3 Person	3 Person
CURB WEIGHT	1,657 lb (751.6 kg)	1,608 lb (729.4 kg)
BED LOAD CAPACITY	1000 lb (453.6 kg)	1000 lb (453.6 kg)
VEHICLE LOAD CAPACITY	1500 lb (680.4 kg)	1500 lb (680.4 kg)
SPEED	25 mph (40.2 kph)	25 mph (40.2 kph)
TOWING CAPACITY	2000 lb (907.2 kg)	2000 lb (907.2 kg)
OUTSIDE CLEARANCE CIRCLE	29.5 ft.	29.5 ft
STEERING & SUSPEN	SION	
STEERING	Rack and Pinion, Tilt Steering Wheel	
FRONT SUSPENSION	Double A-Arm with 10 in (25.4 cm) Travel	
REAR SUSPENSION	Double A-Arm with 9.5 in (24.1 cm) Travel	
SERVICE BRAKE	Dual Piston Front/Single Piston Rear Calipers	
PARKING BRAKE	Parking Gear, Activated Via Shifter	
FRONT/REAR TIRES	25 x 10.5 - 12 All Terrain	

Mars Cars LLC Call us! (714) 847-7673 www.CushmanCalifornia.com