



CUSHMAN®

SHUTTLE™ 6



TRANSPORT LARGE GROUPS EFFICIENTLY.

The Cushman® Shuttle™ 6 is your go-to vehicle for effectively moving people. With the combination of four-forward-facing seats and two rear-facing seats, you can safely transport up to six people comfortably throughout your facility. Available with the option of an energy efficient 72V AC electric drivetrain or a 13.5 hp EFI gas engine, the Shuttle 6 has the stamina necessary to take care of your personnel.

LET'S WORK.®

www.CushmanCalifornia.com

MARS CARS LLC

13.5HP
EFI GAS

72V
AC ELECTRIC
DRIVETRAIN

6
PERSON
SEATING
CAPACITY



CUSHMAN[®] SHUTTLE™ 6



HEADLIGHTS



BENCH SEATING

RACK-AND-PINION
STEERING

OPTIONS & ACCESSORIES

- Rearview Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Pinstripes
- Body Color (Forest Green, White or Custom Options)
- On Board Charger
- Turn Signal with Four-Way Flashers
- Brakelights
- LED Headlights
- CE Kit (gas only)
- Wheel Covers
- Limited Slip Differential
- Trail Tires



COVERED WITH THE 2-YEAR CUSHMAN
CARE TOTAL PROTECTION WARRANTY

	ELECTRIC MODEL	EFI GAS MODEL
BODY & CHASSIS		
FRAME	Welded Steel w/ DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOR	Patriot Blue	
DIMENSIONS		
OVERALL LENGTH	136.0 in (345 cm)	
OVERALL WIDTH	48.5 in (123 cm)	
OVERALL HEIGHT	48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof)	
WHEEL BASE	93.5 in (237 cm)	
WHEEL TRACK	34.2 in (87 cm) Front / 38.0 in (97 cm) Rear	
GROUND CLEARANCE	4.3 in (11 cm)	
POWER		
POWER SOURCE	72V DC	4-Cycle, 24.5 ci (401cc)
VALVE TRAIN	22.4 hp (16.7 kW) Intermittent	Single Cylinder OHV
HORSEPOWER (KW)	72V	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	Six, 12 Volt Deep Cycle	Starter/Generator. Solid State Reg.
BATTERY CHARGER	1000 Watt, 72V, 120/230V VAC UL Listed	One, 12V Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replacable Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	6 Gallon (22.7 L) Tank
SPEED CONTROLLER	350 Amp AC	N/A
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse	Forward - Reverse
REAR AXLE RATIO	17:1	11.47:1 (Forward) 14.35:1 (Reverse)
PERFORMANCE		
SEATING CAPACITY	6-Person	
WEIGHT W/O BATTERIES	964 lb (437 kg)	N/A
CURB WEIGHT	1456 lb (660 kg)	1164 lb (528 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)	
OUTSIDE CLEARANCE CIRCLE	25.5 ft (7.8 m)	
SPEED	16.5 mph ± 0.5 mph (26.4 kph ± 0.8 kph) (High Speed) 12 mph ± 0.5 mph (19.3 kph ± 0.8 kph) (Low Speed)	14 mph ± 0.5 mph (22.5 kph ± 0.8 kph)
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TIRES (FRONT & REAR)	18 x 8.50 - 8 (4 Ply Rated)	

Mars Cars LLC
Call us! (714) 847-7673
www.CushmanCalifornia.com

www.cushman.com

©2019 Textron Specialized Vehicles Inc.
Features and specifications of the vehicles are subject to change without notice.
Vehicle as photographed may include options not included on base model.

82284-G7 (Rev. 12/2018)